

Airtite® TTF

Masonry Coating and Sealant

Uses

Airtite® TTF is a pre-mixed coating for use on stoppings, overcasts and other ventilation controls.

Advantages

- **Fast** - Ready to use straight from the pail or plastic bag.
- **Economical** - One 3-1/2 gallon pail covers approximately 42 ft² at 1/8" thick. One 25 lb plastic bag covers approximately 23 ft² at 1/8" thick.
- **Strong** - Only 1/8" needed to pass MSHA flexural strength and flame spread tests.
- **Reusable** - Unused portion of material can be stored for later use when the pail is resealed.
- **Convenient** - Ready-to-use material is ideal for everyday ventilation control work and patching controls in remote areas.

Description

Airtite® TTF pre-mixed coating is a fiber-reinforced, trowel-grade mine sealant. The fiber reinforcement contains no fiberglass. Its characteristics allow the material to be used over the entire surface of stoppings and overcasts while enabling small- to medium-sized voids and gaps around the perimeter to easily be filled. The product is best applied with a gloved hand or a trowel and stays in a workable state as long as it is handled.

Instructions For Use

1. Build the dry-stacked ventilation control.
2. Open a pail or bag of Airtite® TTF mine sealant.
3. Apply the Airtite® TTF material to the clean blocks using a gloved hand or a trowel.
4. Fill in small to medium sized voids and gaps as needed.
5. Work the coating across the blocks and onto the roof and ribs to form a good seal and bond. Be sure to apply the material slightly heavier along the perimeter where the blocks meet the strata.
6. Clean tools with water and reseal any remaining Airtite® TTF material in the pail for later use.

Packaging

Available in 3-1/2 gallon pails or 25 lb plastic bags, 36 pails per stretch-wrapped pallet and 54 bags per stretch-wrapped pallet.

Shelf Life

One year when stored under cool, dry conditions. Protect from freeze-thaw cycles.

Consult your local Minova representative for additional application information.



Minova Americas Products

Bolts and Plates

Anchoring Products

Pumpable Cementitious Grouts

Airtite® Sealants and Coatings

Chemical Grouts

Minova Americas
150 Carley Court
Georgetown, KY 40324 USA
Phone 800 520 6621
Fax 502 863 1374
Email sales.info@minovaint.com
Web www.minovaamericas.com



A member of the Orica Group

Important Note: Warranty

Minova USA Inc. warrants that its products, at the time of shipment, conform to the applicable descriptions set forth in the invoice and are free from defects in material and workmanship. NO OTHER WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE, SHALL EXIST IN CONNECTION WITH THE SALE OR USE OF ANY MINOVA USA INC. PRODUCT, AND ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED AND EXCLUDED.

All claims under this warranty must be made in writing to Minova USA Inc. within 15 days after discovery of the defect, and within 90 days of the date of shipment by Minova USA Inc. of the product claimed defective. Upon timely receipt of a claim, Minova USA Inc. shall have the option either to inspect the product while in Buyer's possession or to request Buyer to return the product to Minova USA Inc. for inspection. Claims not made as provided above and within the applicable time period will be barred. All warranties shall be null and void if the products have not been stored and used in accordance with procedures recommended by Minova USA Inc.

Minova USA Inc. shall, at its option, either replace the nonconforming or defective product or refund to Buyer its purchase price. The foregoing constitutes Buyer's sole and exclusive remedy for any breach of warranty.