

CEMENTITIOUS GROUTS



Tekrok SCR

Pumpable Bulkhead Construction Cement

Uses

Tekrok SCR pumpable construction cement is ideal for small- to medium-sized construction projects, primarily for water bulkheads. This product is specifically designed to be sulphate- and chloride-resistant. Examples for uses of Tekrok SCR cement include water bulkheads and any job needing a fair-sized pour where thermal cracking could be a problem.

Advantages

- **Fast** – Pumping rate of over 4 yd³ per hour can be achieved
- **Strong** – Over 4,000 psi
- **Convenient** – Can be pumped over 150' through standard 2" mine spray hose; can be pumped directly into standing water
- **Simple** – Powder and water are automatically metered as they are mixed in the placer unit

Description

Tekrok SCR cement was developed in response to customer demand for a sulphate- and chlorate-resistant, high-strength pumpable cement for underground construction projects. It was specifically designed for pumping through our placer unit. The placer meters and mixes the proper amounts of water and powder as it pumps the Tekrok SCR material. Fifty-four 50 lb bags of Tekrok SCR powder are used per cubic yard.

The material has a pumping life of up to 30 minutes and sets in 5 to 8 hours. Tekrok SCR cement is especially suited for small- to medium-sized construction projects and also for projects where the convenience of a pumpable cement is required.

Consult your local Minova representative for additional application information.

Shelf Life

Twelve months in dry conditions.

Instructions For Use

To calibrate the placer unit and to make adjustments to the water supply, it is highly recommended that a consultant from Minova, or an authorized contractor, be on site to advise mine personnel, especially during the pumping process.

1. Build forms around the site.
2. Level and fill the site as necessary.
3. Run a 2" hose from the placer to the job site.
4. Hook up fresh water at the rate of 10 gpm at a minimum of 50 psi, and AC power, to the placer.
5. Adjust water and powder feed so that 3 gallons of water are used for every 2 bags (3.3 gal/100 lbs) of Tekrok SCR cement.
6. Pump the material into the forms, leveling as needed.

Continued >

Tekrok SCR

Placer - Made in the USA by Minova; Multi-use placer unit is used to transfer several of Minova's cementitious products: Tekseal®, Tekfoam, Tekcrib, Tekrok

Motor: 15 hp AC; Full load amps - 21 @ 460V, 18 @ 575V.; Cable Size: normally #6 (permissible unit available).

Develops 200+ psi, and typically pumps Tekrok SCR cement 150' through a 2" hose. Requires 10 gpm @ 50 psi

Dimensions: 3'6" x 2'3" x 11'9";

Wgt: 1,700 lbs;

Unit capacity with Tekrok SCR: over 4 yds³/hour.

Packaging

50 lb, 3-ply bags with 1 polyethylene layer, 56 bags per stretch-wrapped pallet.

Minova Americas Products

Bolts and Plates

Anchoring Products

Pumpable Cementitious Grouts

Airtite® Sealants and Coatings

Chemical Grouts



Minova Americas

150 Carley Court

Georgetown, KY 40324 USA

Phone 800 520 6621

Fax 502 863 1374

Email sales.info@minovaint.com

Web www.minovaamericas.com



A member of the Orica Group

Important Note: Warranty

Minova USA Inc. warrants that its products, at the time of shipment, conform to the applicable descriptions set forth in the invoice and are free from defects in material and workmanship. NO OTHER WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE, SHALL EXIST IN CONNECTION WITH THE SALE OR USE OF ANY MINOVA USA INC. PRODUCT, AND ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED AND EXCLUDED.

All claims under this warranty must be made in writing to Minova USA Inc. within 15 days after discovery of the defect, and within 90 days of the date of shipment by Minova USA Inc. of the product claimed defective. Upon timely receipt of a claim, Minova USA Inc. shall have the option either to inspect the product while in Buyer's possession or to request Buyer to return the product to Minova USA Inc. for inspection. Claims not made as provided above and within the applicable time period will be barred. All warranties shall be null and void if the products have not been stored and used in accordance with procedures recommended by Minova USA Inc.

Minova USA Inc. shall, at its option, either replace the nonconforming or defective product or refund to Buyer its purchase price. The foregoing constitutes Buyer's sole and exclusive remedy for any breach of warranty.